



Republic Brass Sales, Inc.
 619.229.8304
 6566 Federal Blvd
 Lemon Grove, CA 91945
 www.republicbrasssales.com

FUEL HOSE MEDIUM PRESSURE HIGH-TEMP HOSE

Specification: Fire Resistant per USCG SAE J1942

Pressure Rating: 400 - 1500 PSI

Sizes: 5/16" - 1"

Application: Hydraulic, crude, fuel and lubricating oils, gasoline, water and phosphate-ester based hydraulic fluids

Operating Temperature Range: -40°F to +300°F

FITTING REFERENCE: MIL-F-24787


SAE 37°:
 411-RBS

CPV:
 190911-RBS
 191301-RBS

FLANGE:
 190109-RBS
 190016-RBS
 190124-RBS
 190103-RBS

SPLIT CLAMP:
 FC9423-RBS
 FC9424-RBS
 FC9425-RBS
 FC9426-RBS

DOGLEG:
 191302-RBS
 190093-RBS



RBS234
 EQUAL TO AEROQUIP P/N FC234

CONSTRUCTION: ELASTOMER TUBE, BRASS PLATED STEEL WIRE REINFORCEMENT, BRAIDED REFRACTORY INSULATION AND BLUE ELASTOMER COVER

RBS P/N	EQUAL TO AEROQUIP NUMBER	HOSE SIZE	HOSE O.D.	WORKING PRESSURE	MIN. BEND RADIUS	WEIGHT/FT.
RBS234-5	FC234-5	5/16	0.58	1,500 PSI	1.00	0.22
RBS234-6	FC234-6	3/8	0.68	1,500 PSI	1.25	0.25
RBS234-8	FC234-8	1/2	0.76	1,250 PSI	1.75	0.30
RBS234-10	FC234-10	5/8	0.94	1,250 PSI	2.25	0.45
RBS234-12	FC234-12	3/4	1.08	750 PSI	2.75	0.48
RBS234-16	FC234-16	1	1.24	400 PSI	3.50	0.51

