



Republic Brass Sales, Inc.  
 619.229.8304  
 6566 Federal Blvd  
 Lemon Grove, CA 91945  
 www.republicbrasssales.com

# HOSE HIGH PRESSURE AIR MIL-H-24135/5

Specification: MIL-H-24135/5

Pressure Rating: 1125 - 5000 PSI

Sizes: 1/4" - 2"

FITTING REFERENCE:  
 MIL-F-24787

SAE 37°:  
 4721-RBS

CPV:  
 190909-RBS  
 191304-RBS

FLANGE:  
 FC9506-RBS  
 FC9224-RBS

DOGLEG:  
 191305-RBS

Application: For pneumatic applications. Perforated cover prevents blistering, assures better high pressure service  
 Operating Temperature Range: -40°F to +212°F



MIL-H-24135/5  
 EQUAL TO AEROQUIP P/N AE371

CONSTRUCTION: SYNTHETIC RUBBER TUBE, DOUBLE WIRE BRAID REINFORCEMENT, TEXTILE BRAID AND PERFORATED SYNTHETIC RUBBER COVER

RBS P/N	EQUAL TO AEROQUIP NUMBER	HOSE I.D.	WORKING PRESSURE	BURST PRESSURE	MIN. BEND RADIUS	WEIGHT/FT.
24135/5-4	AE371-4	1/4	5,000 PSI	20,000 PSI	4.00	0.34
24135/5-6	AE371-6	3/8	4,000 PSI	16,000 PSI	5.00	0.44
24135/5-8	AE371-8	1/2	3,500 PSI	14,000 PSI	7.00	0.64
24135/5-10	AE371-10	5/8	2,750 PSI	11,000 PSI	8.00	0.65
24135/5-12	AE371-12	3/4	2,250 PSI	9,000 PSI	9.50	0.82
24135/5-16	AE371-16	1	2,000 PSI	8,000 PSI	12.00	1.00
24135/5-20	AE371-20	1 1/4	1,625 PSI	6,500 PSI	16.50	1.95
24135/5-24	AE371-24	1 1/2	1,250 PSI	5,000 PSI	20.00	2.02
24135/5-32	AE371-32	2	1,125 PSI	4,500 PSI	25.00	2.70

